

<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <div style="border: 1px solid black; padding: 2px; width: 40px; text-align: center;">VHM</div> <div style="border: 1px solid black; padding: 2px; width: 40px; text-align: center; background-color: #800040; color: white;">AT</div> <div style="border: 1px solid black; padding: 2px; width: 40px; text-align: center;">DIN 6537</div> </div> <div style="text-align: center;"> </div> <div style="margin-left: 20px;"> <div style="color: red; font-weight: bold; font-size: 1.2em;">1300</div> </div> </div>													
Material groups													
<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="background-color: #ADD8E6;">P</td> <td style="background-color: #FFD700;">M</td> <td style="background-color: #FF6347;">K</td> </tr> <tr> <td style="background-color: #90EE90;">N</td> <td style="background-color: #FFA07A;">S</td> <td style="background-color: #D3D3D3;">H</td> </tr> </table>								P	M	K	N	S	H
P	M	K											
N	S	H											
Execution													
90°													
Quality of material													
VHM													
Coating													
AT													
Ø d <sub>1</sub>	M	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	Ø d <sub>2</sub>	Ø d <sub>2</sub> h6	Norm	~DIN-6537					
							Tol.	m7					
							INDEX	W9-704010					
2,50	M3	62	20	8,8	6	6	0250	●					
3,30	M4	62	24	11,4	6	6	0330	●					
4,20	M5	66	28	13,6	6	6	0420	●					
5,00	M6	79	34	16,5	8	8	0500	●					
6,80	M8	89	47	21,0	10	10	0680	●					
8,50	M10	102	55	25,5	12	12	0850	●					
10,20	M12	107	60	30,0	14	14	1020	●					
12,00	M14	115	65	34,5	16	16	1200	●					
14,00	M16	123	73	38,5	18	18	1400	●					

