

ISO Metric coarse thread DIN-13


Set of gauges on page 210



LH

6G



Symbol	P	Tol	MSBg	MSBg LH	MSBg	MSRh	MSRk
			GO / NOGO	GO / NOGO	GO / NOGO	GO	NOGO
M		INDEX	S3-302161	S3-301161	S3-302162	Y3-412162	Y3-422162
M 1	0,25	0010	●	○	○	●	●
M 1,2	0,25	0012	●	○	○	●	●
M 1,4	0,3	0014	●	○	○	●	●
M 1,6	0,35	0016	●	○	○	●	●
M 1,7	0,35	0017	●	○	○	●	●
M 1,8	0,35	0018	●	○	○	●	●
M 2	0,4	0020	●	○	○	●	●
M 2,2	0,45	0022	●	○	○	●	●
M 2,5	0,45	0025	●	○	○	●	●
M 2,6	0,45	0026	●	○	○	●	●
M 3	0,5	0030	●	●	○	●	●
M 3,5	0,6	0035	●	○	○	●	●
M 4	0,7	0040	●	●	○	●	●
M 4,5	0,75	0045	●	○	○	●	●
M 5	0,8	0050	●	●	○	●	●
M 6	1	0060	●	●	○	●	●
M 7	1	0070	●	○	○	●	●
M 8	1,25	0080	●	●	○	●	●
M 9	1,25	0090	●	○	○	●	●
M 10	1,5	0100	●	●	○	●	●
M 12	1,75	0120	●	●	○	●	●
M 14	2	0140	●	●	○	●	●
M 16	2	0160	●	●	○	●	●
M 18	2,5	0180	●	●	○	●	●
M 20	2,5	0200	●	●	○	●	●
M 22	2,5	0220	●	●	○	●	●
M 24	3	0240	●	●	○	●	●
M 27	3	0270	●	●	○	●	●
M 30	3,5	0300	●	●	○	●	●
M 33	3,5	0330	●	●	○	●	●
M 36	4	0360	●	●	○	●	●
M 39	4	0390	●	○	○	●	●
M 42	4,5	0420	●	○	○	●	●
M 45	4,5	0450	●	○	○	●	●
M 48	5	0480	●	○	○	●	●
M 52	5	0520	●	○	○	●	●

Go gauges above M52 are called MSCh and no go MSCk and they are produced with separate handle.