


HOLE TOLERANCE 0/+0.25mm



DRS 3XD			DC	DCON	OAL	LF	LB	ADJLX max. radial offset	PL hole bottom shape	MIID
----------------	--	--	-----------	-------------	------------	-----------	-----------	---	-------------------------------------	-------------

05	NT-DRS-3D	D12.50-S20-05	●	12.5	20	107	57	39	0.50	0.40	SPMX05 SPGX05
		D13.00-S20-05	●	13	20	107	57	39	0.50	0.40	
		D13.50-S20-05	●	13.5	20	110	60	42	0.50	0.40	
		D14.00-S20-05	●	14	20	110	60	42	0.50	0.40	
		D14.50-S20-05	●	14.5	20	114	64	45	0.50	0.40	
06	NT-DRS-3D	D15.50-S25-06	●	15.5	25	124	68	48	0.50	0.50	SPMX06 SPGX06
		D16.00-S25-06	●	16	25	124	68	48	0.50	0.50	
		D16.50-S25-06	●	16.5	25	127	71	51	0.50	0.50	
		D17.00-S25-06	●	17	25	127	71	51	0.50	0.50	
		D17.50-S25-06	●	17.5	25	131	75	54	0.50	0.50	
		D18.00-S25-06	●	18	25	131	75	54	0.50	0.50	
		D18.50-S25-06	●	18.5	25	134	78	57	0.50	0.50	
		D19.00-S25-06	●	19	25	134	78	57	0.50	0.50	
		D19.50-S25-06	●	19.5	25	139	83	60	0.50	0.50	
		D20.00-S25-06	●	20	25	139	83	60	0.50	0.50	
		D20.50-S25-06	●	20.5	25	142	86	63	0.25	0.50	
		D21.00-S25-06	●	21	25	142	86	63	0.25	0.50	
		D21.50-S25-06	●	21.5	25	145	89	66	0.25	0.50	
07	NT-DRS-3D	D22.00-S25-07	●	22	25	145	89	66	0.50	0.50	SPMX07 SPGX07
		D22.50-S32-07	●	22.5	32	154	94	69	0.50	0.50	
		D23.00-S32-07	●	23	32	154	94	69	0.50	0.50	
		D23.50-S32-07	●	23.5	32	158	98	72	0.50	0.50	
		D24.00-S32-07	●	24	32	158	98	72	0.50	0.50	
		D24.50-S32-07	●	24.5	32	162	102	75	0.50	0.50	
		D25.00-S32-07	●	25	32	162	102	75	0.50	0.50	
		D25.50-S32-07	●	25.5	32	165	105	78	0.50	0.60	
		D26.00-S32-07	●	26	32	165	105	78	0.25	0.60	
		D26.50-S32-07	●	26.5	32	168	108	81	0.25	0.60	
		D27.00-S32-07	●	27	32	168	108	81	0.25	0.60	
09	NT-DRS-3D	D27.50-S32-07	●	27.5	32	172	112	84	0.25	0.60	SPMX09 SPGX09
		D28.00-S32-09	●	28	32	172	112	84	0.50	0.80	
		D28.50-S32-09	●	28.5	32	175	115	87	0.50	0.80	
		D29.00-S32-09	●	29	32	175	115	87	0.50	0.80	
		D29.50-S32-09	●	29.5	32	181	121	90	0.50	0.80	
		D30.00-S32-09	●	30	32	181	121	90	0.50	0.80	
		D31.00-S32-09	●	31	32	185	125	93	0.25	0.80	
D32.00-S32-09	●	32	32	188	128	96	0.25	0.80			
D33.00-S32-09	●	33	32	192	132	99	0.25	0.80			

● stock standard

TURNING

THREADING

GROOVING

MILLING

DRILLING

ACCESSORIES