



<b>DRS 4XD</b>			<b>DC</b>	<b>DCON</b>	<b>OAL</b>	<b>LF</b>	<b>LB</b>	<b>ADJLX max. radial offset</b>	<b>PL hole bottom shape</b>	<b>MIID</b>
----------------	--	--	-----------	-------------	------------	-----------	-----------	---	-------------------------------------	-------------

05	NT-DRS-4D	D12.50-S20-05	●	12.5	20	120	70	52	0.50	0.40	SPMX05 SPGX05
		D13.00-S20-05	●	13	20	120	70	52	0.50	0.40	
		D13.50-S20-05	●	13.5	20	124	74	56	0.50	0.40	
		D14.00-S20-05	●	14	20	124	74	56	0.50	0.40	
		D14.50-S20-05	●	14.5	20	129	79	60	0.50	0.40	
06	NT-DRS-4D	D15.50-S25-06	●	15.5	25	140	84	64	0.50	0.50	SPMX06 SPGX06
		D16.00-S25-06	●	16	25	140	84	64	0.50	0.50	
		D16.50-S25-06	●	16.5	25	144	88	68	0.50	0.50	
		D17.00-S25-06	●	17	25	144	88	68	0.50	0.50	
		D17.50-S25-06	●	17.5	25	149	93	72	0.50	0.50	
		D18.00-S25-06	●	18	25	149	93	72	0.50	0.50	
		D18.50-S25-06	●	18.5	25	153	97	76	0.50	0.50	
		D19.00-S25-06	●	19	25	153	97	76	0.50	0.50	
		D19.50-S25-06	●	19.5	25	159	103	80	0.50	0.50	
		D20.00-S25-06	●	20	25	159	103	80	0.50	0.50	
		D20.50-S25-06	●	20.5	25	163	107	84	0.25	0.50	
		D21.00-S25-06	●	21	25	163	107	84	0.25	0.50	
		D21.50-S25-06	●	21.5	25	167	111	88	0.25	0.50	
07	NT-DRS-4D	D22.00-S25-07	●	22	25	167	111	88	0.50	0.50	SPMX07 SPGX07
		D22.50-S32-07	●	22.5	32	177	117	92	0.50	0.50	
		D23.00-S32-07	●	23	32	177	117	92	0.50	0.50	
		D23.50-S32-07	●	23.5	32	182	122	96	0.50	0.50	
		D24.00-S32-07	●	24	32	182	122	96	0.50	0.50	
		D24.50-S32-07	●	24.5	32	187	127	100	0.50	0.50	
		D25.00-S32-07	●	25	32	187	127	100	0.50	0.50	
		D25.50-S32-07	●	25.5	32	191	131	104	0.50	0.60	
		D26.00-S32-07	●	26	32	191	131	104	0.25	0.60	
		D26.50-S32-07	●	26.5	32	195	135	108	0.25	0.60	
		D27.00-S32-07	●	27	32	195	135	108	0.25	0.60	
D27.50-S32-07	●	27.5	32	200	140	112	0.25	0.60			
09	NT-DRS-4D	D28.00-S32-09	●	28	32	200	140	112	0.50	0.80	SPMX09 SPGX09
		D28.50-S32-09	●	28.5	32	204	144	116	0.50	0.80	
		D29.00-S32-09	●	29	32	204	144	116	0.50	0.80	
		D29.50-S32-09	●	29.5	32	211	151	120	0.50	0.80	
		D30.00-S32-09	●	30	32	211	151	120	0.50	0.80	
		D31.00-S32-09	●	31	32	216	156	124	0.25	0.80	
		D32.00-S32-09	●	32	32	220	160	128	0.25	0.80	
		D33.00-S32-09	●	33	32	225	165	132	0.25	0.80	

● stock standard

TURNING

THREADING

GROOVING

MILLING

DRILLING

ACCESSORIES